

技术资料书

聚乙烯酯 (PEN) 薄膜胶带 产品编号 : BTEN2



说明 : BTEN2 PEN 胶带是在 Teonex® Q51 PEN 聚乙烯酯 (PEN) 薄膜涂覆一层丙烯酸酯胶粘剂而成。在 180°C 环境下, 拥有极佳的热性能, 应用领域广泛。它具有较高的温度等级, 在高温环境下, 具有良好的尺寸稳定性、抗水解性和透氧性。

用途 : 高性能电气应用, 适用于高温线圈, 如牵引电机、发电机、电容器和变压器等。PEN 胶带可用于 F 等级 155 °C、H 等级 180 °C 和 N 等级 200 °C 绝缘系统的主组绝缘。

性能	单位	规格
颜色	-	透明或黑色
总厚度	mm	0.055 ± 0.005
拉伸强度	kg/25mm	12
伸长率	%	90
黏着力	kg/25mm	0.6
击穿电压	kV	6
温度等级	°C	155

*Teonex® 是杜邦帝人公司的注册商标

*P. LEO® 是彼利奥公司的注册商标

测试方法 : 根据 ASTM 标准测试

保存期限 : 6 个月 (温度: 73°F、湿度: 65%)

包装标准 : 每卷长 50M, 宽 2mm - 1000mm, 卷心直径 3 英寸

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

仅供参考, 如与英文版有歧异之处, 一切内容以英文版为准。

